



STAY CONNECTED... WITH OUR PRIME ATA CATM



The Prime ATA CATM is designed as an ideal solution for lone worker, vehicle, pet and asset tracking applications. The thumb sized button makes this device ideal for applications requiring rapid notification of emergency alert or regular setting of geo-fences based on current location.

Our Prime ATA CATM features an SOS button, superior GPS performance, 3-axis accelerometer, and Wi-Fi tracking.



Call **1.888.538.3489**
or visit our website at:
www.micronwireless.com

Micron Electronics, LLC
1001 Yamato Rd., Suite 400
Boca Raton, FL 33431
P. 888.538.3489
www.micronwireless.net

© 2018 Micron Electronics. A subsidiary of Micron Holdings. All rights reserved.
Prime is a trademark of Micron Electronics.

Prime ATA CATM SPECIFICATIONS



KEY FEATURES

- Wi-Fi
- Super Sensitive GPS
- Built in 3-axis Accelerometer for Motion Alert with configurable thresholds
- Internal LED Indicator: Cellular, GPS, Wi-Fi and battery status

CELLULAR

- Data Support LTE CATM1 packet data, SMS
- Operating Bands
LTE CATM1 (AT&T)

LOCATION TECHNOLOGY

- GPS & GLONASS
SBAS: WAAS, EGNOS, MSAS, GAGAN
- Location Accuracy 2.5 meter CEP (with SBAS)
- Tracking Sensitivity -162dBm
- Acquisition Sensitivity -147dBm

BATTERY LIFE

- Without Reporting 720 Hours
- One Report per 5 Minutes 360 Hours
- One Report per 30 Minutes 562 Hours

ENVIRONMENTAL

- Temperature -20° to 55° C (operating);
-40° to +85°C (storage)
- Humidity 95%RH @ 50° C non-condensing
- RoHS Compliant

ELECTRICAL

- Operating Voltage 3.7V internal battery pack
- Power Consumption
Typical 200µA @ 3.7V (deep sleep)
Typical 21.5 mA @ 3.7V
(UDP connection, GPS off)
Typical 89.9 mA @ 3.7V (continuous transmit)

PHYSICAL

- Dimensions 70 x 41.5 x 27 (mm)
- Battery 2600mAh Rechargeable Li-Polymer battery
- SIM 4FF

DEVELOPMENT SUPPORT OPTIONS

- Customized hardware and software development available upon request.

PROGRAMMING & MANAGEMENT TOOLS

- MAP Utility

